

Water Heater Relief Valves

Pressure Relief Valves - Tankless Water Heater



- Pressure relief valves used in residential applications to protect against excessive pressure on domestic storage tanks and tankless water heaters
- Bronze body with NPT male inlet and NPT female outlet
- Features a stainless steel spring and test lever
- Can be used with Watts Series 210 gas shutoff valve to shut off gas to heater if temperature exceeds 99C (210F)
- ASME rated and CSA listed

Size	PSIG	Brand	Part Number
3/4"	125	Watts	3L-125
3/4"	150	Watts	3L-150

Temperature & Pressure Relief Valves - Electric Water Heater



- Automatic temperature and pressure relief valves used in electric water heaters
- Bronze body with NPT male inlet and NPT female outlet
- Features unique non-metallic coating which protects the element against galvanic and electromechanical corrosion by isolating it from the heated water
- Temperature Relief: 99C (210F)

Size	Element Length	Btu/Hour	PSIG	Brand	Part Number
1/2"	4"	15,000	150	Conbraco	18-401-30

Temperature & Pressure Relief Valves - Residential Gas Water Heater



100XL4-150



L100XL3-150
Extended Shank

- Self-closing, automatic relief valves used in water heater and hot water storage tank applications to provide temperature and pressure protection to hot water supply tanks and hot water heaters
- Bronze body with NPT male inlet and NPT female outlet
- Features a unique thermostat with a special thermo-bonded coating and test lever
- Temperature Relief: 99C (210F)
- ASME rated and CSA listed
- **L100XL3-150** has a 1 1/2" extended shank for water heaters with up to 2" of insulation, which eliminates the use of an extension nipple

Size	Element Length	Btu/Hour	PSIG	Brand	Part Number
3/4" NPT	2"	80,000	150	Watts	10L2-150
3/4" NPT	3"	100,000	150	Watts	100XL4-150
3/4" NPT	3"	100,000	150	Watts	L100XL3-150

Temperature & Pressure Relief Valves - Commercial Gas Water Heater



- Automatic re-seating relief valves used in commercial water heater applications to provide automatic temperature and pressure protection to hot water supply tanks and hot water heaters
- Bronze body with NPT male inlet and NPT female outlet
- Features a unique thermostat with a special thermo-bonded coating, tamper resistant bonnet screws, test lever and an extension thermostat for installation in the hot water outlet within the allowable distance from the top of the tank
- Temperature Relief: 99C (210F)
- ASME rated and CSA listed

Size	Element Length	Btu/Hour	PSIG	Brand	Part Number
1"	4"	500,000	125	Watts	40XL4-125
1"	4"	500,000	150	Watts	40XL4-150
3/4"	5"	205,000	150	Watts	40XL5-150



**Water Heater
Elements & Accessories**