

Water Gauge & Accessories

Standard Pattern Water Gauge - Bronze



20-150-00



H6-50 & H6-55



H6-10

- Use for all types of liquid level verification
- MNPT pipe connections
- Aluminum wheel
- **Includes** 2 check valves, 2 brass guard rods, 2 rubber washers, & glass tube
- Standard 1/4" needle drain valve in lower arm

Pipe Size	Glass		WT/100 Lbs. / kg	Brand	Part Number
	O.D.	Length			
1/2"	5/8"	12"	160 / 72.6	Conbraco	20-150-00

Replacement Parts	
Description	Part Number
5/8" ID x 7/8" OD, high pressure lip mold gasket (#3)	H6-50
3/4" ID x 1 9/64" OD, high pressure lip mold gasket (#33)	H6-55
9/16" ID x 13/16" OD x 1/4" Thickness, square cut neoprene gasket	H6-10
5/8" rubber washer	D-1600-00

Tubular Gauge Glass - Standard & Red Lined



Clear Glass



Red-Lined Glass

Size	Length	Max Working Pressure (psi)		Part Number
		Temp. Up to 66C (150F) No Corrosion	Steam Boiler Service Up to 218C (425F)	
Standard Glass				
5/8" OD +0,-3/64" Wall 5/64", ±1/64"	10"	205	100	5/8X10
	12"	200	100	5/8X12
	18"	190	100	5/8X18
	24"	185	100	5/8X24
Red-Lined Glass				
5/8" OD +0,-1/32" Wall 3/32", ±1/64"	10"	345	280	5/8X10RED
	12"	335	280	5/8X12RED
	18"	305	265	5/8X18RED
	24"	265	255	5/8X24RED

Cutter Tools



T100-330



T100-370



Description	Part Number
Gauge Glass Cutter - Gauge glass cutter for standard, Red Line & High Pressure glass. Leaves clean, straight edges.	T100-330
Porcelain & Gauge Glass Cutter - Hardened and tempered cutting wheels, sure-grip molded handles, hardened steel jaws, locking clasp, adjustable stop. Also cuts gauge glass up to 3/4" in diameter (do not cut Red Line or High Pressure with this tool)	T100-370