

Tapes

Insulation Tape - Cork & Foam



Description	Size	Part Number
Cork Insulation Tape Adheres firmly to all metals. Use on hot or cold pipes to stop condensation and drips. Black.	1/8" x 2" x 30'	6-330
Foam Insulation Tape Easily cut and molded, self-adhesive. Use on hot or cold pipes. Fits well around valves and fittings.	1/8" x 2" x 30'	6-9718

Pipe Wrap Tape - Polyethylene



- Ideal for protection of underground and above ground pipelines and meets the Uniform Plumbing Code as per IAPMO standards PS 37-90 for pipe wrapping
- Excellent corrosion, UV and abrasion resistance
- Long lasting butyl rubber based adhesive
- High humidity resistance
- Excellent dielectric strength - 12,000 Volts
- Heavy duty polyethylene film

Size	Part Number
48mm x 30m	583-01

Sheathing Tape for PE Vapor Barrier



- Designed to seal joints and seams of PE Vapor Barrier
- High tack adhesive provides aggressive contact
- Outstanding adhesion on polyethylene
- Strong and durable holding power
- Water, moisture and mold resistant
- Prevents air infiltration
- 30 lb/in tensile strength
- Made of UV resistant polypropylene film and coated with a specially formulated solvent based acrylic adhesive
- The only CCMC evaluated method to seal/seam polyethylene vapor barrier film

Size	Part Number
60mm x 55m x 4.1 mil	219-08

Tapes

Splicing Tape



- Flexible, self-fusing rubber electrical insulating tape
- Used for low voltage electrical insulating and moisture sealing applications
- Temperature range -10C to 80C (14F to 176F)

Size	Part Number
19.05mm x 6.04m x 20mil	ETSBR

Teflon Tape



- Pipe thread tape provides a strong tight seal for any threaded joint and permits easy disassembly
- Yellow gas seal tape is UL listed

Size	Part Number
Pink - 1.2 g/cm3 density - 1/2" x 260" x 0.094"	TT260-PP
White - 0.35 g/cm3 density - 1/2" x 480" x 0.003"	3213-103
Yellow (Gas) - 1.2 g/cm3 density - 1/2" x 480" x 0.094"	3203-480

Wire - Mechanics Stove Pipe



- 18 gauge soft annealed wire
- Used for general purpose repair work

Size	Part Number
2lb spool, 330'	SPW2