



2018

Spring &
Summer
Pump & Water
Treatment
Program

Pump &
Well

Water
Treatment

Drives

Liquid Level
Controls

Well Tanks

CALGARY
6 - 2320 35th Ave NE
403.244.2161
800.661.1346
cgyorders@daviessg.com

LETHBRIDGE
2 - 1710 36th Street N
403.381.7707
877.595.7707
laorders@daviessg.com

SASKATOON
602 48th Street E
306.933.2433
877.355.3377
skorders@daviessg.com



2018 Spring & Summer Pump & Water Treatment Program

PLACE YOUR ORDERS TODAY BY CALLING OR EMAILING:

CALGARY	403-244-2161	800-661-1346	cgyorders@daviessg.com
LETHBRIDGE	403-381-7707	877-595-7707	laorders@daviessg.com
SASKATOON	306-933-2433	877-355-3377	skorders@daviessg.com

Visit Our Website: www.daviessg.com

- Easy to Navigate
- Extensive Product Catalogue
- New Product Information
- Special Announcements
- Supplier Brands with Links to Websites
- Submit an Order, Question or Comment
- Request a Quote
- Company Information
- Branch Addresses and Contact Information



BRANDS REPRESENTED



PENTEK INTELLIDRIVE™ CONSTANT PRESSURE CONTROLLERS



Constant Pressure for Well Pump Systems

- Maintains constant & consistent water pressure for residential well pump systems by automatically adjusting motor speeds to meet changes in water demand
- For use with both submersible and above ground well pumps
- Fully programmable with 34 adjustable programming parameters
- Extends the life of the pump and motor by using "Soft Start / Coast to Stop" as well as eliminating frequent on/off pressure cycling
- Keypad with backlit LCD display has diagnostic and status indicators
- Removable/ replaceable terminal blocks
- Detects and displays when there is a grounding problem and shuts down the system until problem is corrected
- Includes: Variable Frequency Drive with NEMA 3R outdoor enclosure, Transducer (1/4" thread size, 18 NPT type) & Transducer Cable (10')

Motor Type	HP Range	Input Voltage	Max Output Amps	Part Number
2 Wire* 1 Phase	0.5 to 1 HP	190V to 265V	9.5A	PID10
3 Wire* 1 Phase			7.5A	
3 Phase			5A	
2 Wire* 1 Phase	0.5 to 1.5 HP	190V to 265V	11A	PID20
3 Wire* 1 Phase	0.5 to		13.5A	
3 Phase	2 HP		8.5A	

2 Wire Applications Only Compatible with PENTEK brand 2-Wire Motors
 * Select drive by Service Factor amps of pump motor



PENTEK INTELLIDRIVE™ SURGE PROTECTION KIT

Description	Part Number
Line & Load Side Surge Protection for use with any 230 Volt PENTEK Drive	VFD-SGA
One surge protection kit must be installed with each IntelliDrive™ Controller to preserve the Drive's warranty	

4" SUBMERSIBLE PUMPS



GPM	HP	Volts	Stages	Wire	Discharge Head	Part Number
STA-RITE®						
10	1/2	230	6	3		S10P4HS05231
10	3/4	230	8	3	Stainless Steel	S10P4HS07231
10	1	230	11	3		S10P4HS10231
J-Class TRI-SEAL™						
10	1/2	230	6	3		9376-1035
10	3/4	230	8	3	Stainless Steel	9376-1040



Larger HP Pumps Available!

CONTROL BOXES



Accepts the Pumpteck Quick Disconnect						
HP	KW	Volts	Hz	Terminals	Wiring	Part Number
1/2	.37	230	60	5	Up to #10 AWG	280-1054-915
3/4	.55	230	60	5	Up to #10 AWG	280-1074-915
1	.75	230	60	5	Up to #10 AWG	280-1084-915



HEAT SHRINK SPLICE KIT

Inside Dia Max	Wall	Part Number
0.15"	0.08"	HS4

SHALLOW WELL JET PUMPS - CAST IRON

HP	Volts	Switch Setting	Suction x Discharge	Brand	Part Number
1/2	115/230	30-50 psi	1 1/4" x 1"	Sta-Rite	SNC
3/4	115/230	30-50 psi	1 1/4" x 1"	Sta-Rite	SND
1/2	115/230	30-50 psi	1 1/4" x 1"	J-Class VersaJet Pro™	9118-1005
1/2	115/230	30-50 psi	1 1/4" x 1"	J-Class VersaJet™	9118-0005

CONVERTIBLE DEEP WELL JET PUMPS - CAST IRON

HP	Volts	Switch Setting	Suction x Discharge	Drive	Brand	Part Number
1/2	115/230	30-50 psi	1 1/4" x 1"	1"	Sta-Rite	SLC
1/2	115/230	30-50 psi	1 1/4" x 3/4"	1"	J-Class	9106-0020
3/4	115/230	30-50 psi	1 1/4" x 3/4"	1"	J-Class	9106-0053



JET PUMP & TANK PACKAGE



Jet Pump	Total Tank Volume	Draw Down @ 30/50 psi	Package Part Number
J-Class Pump #9118-0005	5.3gal / 20L	1.6gal / 6.2L	VJ0520PK

Includes: Jet Pump, Horizontal Pressure Tank, Pressure Gauge, Pressure Switch, Hose & Fittings

- ✓ For shallow well applications
- ✓ Ideal for cottage & acreage use
- ✓ Each package comes pre-assembled

PRESSURE TANKS



PJR Series



WR Series



FL Series



FLU Series

Total Volume		Dia. x Height (Inches)	Drawdown @ 30-50 PSI		Part Number
Gal	L		Gal	L	
Steel Tanks For General Purpose Water Systems					
2.1	8	8 x 12	0.7	2.5	PJR6
4.8	18	11 x 14.5	1.5	5.6	PJR15
5.3	20	11.4 x 17.5	1.6	6.2	PJR20S*
9.0	32	12.5 x 18.9	2.6	9.8	PJR25S*
20	80	16 x 29	6.8	25.8	WR60R
26	100	16 x 34.5	8.9	33.6	WR80R
33	130	16 x 42.75	11.3	42.6	WR120R
44	170	21 x 36.25	15	56.8	WR140R
81	310	21 x 62	27.6	104.5	WR240R
Fibrewound Tanks For General Purpose Water Systems					
22	83.3	16.5 x 34.1	7.5	27.2	FL7
35	132.5	16.5 x 48.9	11.9	44.2	FL12
Stainless Steel VFDA Tank For Constant Pressure Systems					
5.0	18.9	10.6 x 16.2	1.8	6.8	PS5-S02**

*Horizontal Tank with Mounting Bracket **PS5-S02 is Steel (not Stainless Steel)

RETENTION TANKS

Total Volume		Overall Height	Floor to CL Height	Dia.	System Connection		Part Number
Gal	Litres				Top	Bottom	
40	151	53.4"	1.75"	16.5"	1 1/4"	1 1/4"	FLU40EZ
80	303	64.1"	2.25"	21.4"	1 1/4"	1 1/4"	FLU80EZ



SUBMERSIBLE SUMP (UTILITY) PUMPS - 115 VOLT

HP	Max GPM	Max Head	Switch Type	Discharge	Cord	Part Number
1/6	20	26'	Manual On/Off	1" FNPT	10'	505486
1/6	20	26'	Piggy-back Diaphragm	1" FNPT	10'	505300
1/4	40	25'	Snap Action Float	1 1/4" FNPT	10'	505700
1/3	70	24'	Piggyback Float	1 1/2" NPT	8'	MS33PT10
1/3	70	24'	Vertical Float	1 1/2" NPT	8'	MS33PV10
1/2	70	24'	Vertical Float	1 1/2" NPT	8'	MS50PV10



505486 Water Wizard®



505300



505700 Snappy John®



MS Series



SUBMERSIBLE SUMP PUMPS - CAST IRON - 115 VOLT

HP	Max GPM	Max Head	Switch Type	Discharge	Cord	Part Number
1/3	52	20'	Vertical Float	1 1/2" FNPT	10'	506422
1/3	52	20'	Wide Angle Float	1 1/2" FNPT	10'	506424
1/3	49	24'	Vertical Float	1 1/2" NPT	10'	MDC33V1
1/3	49	24'	Piggyback Float	1 1/2" NPT	10'	MDC33P1
1/2	62	33'	Piggyback Float	1 1/2" NPT	20'	MDC50PC1
1/2	62	33'	Vertical Float	1 1/2" NPT	20'	MDC50VC1



506422



506424

Little GIANT

Myers®



MDC

AUTOMATIC SUMP PUMP BATTERY BACKUP SYSTEMS



MBSP-2

Myers



MBSP-3C

Link2O

Performance Per Charge with BAT75*:
3.5 Days (7000 GAL/3.5 Hour Continuous)
Performance Per Charge with BAT40*:
1.5 Days (2900 GAL/3.0 Hour Continuous)
Max Flow: 34 GPM
Flow @ 10': 10 GPM
Max Lift: 13'

Includes: Backup pump, reed activation switch, AC power supply, integrated control panel and battery case, 1 1/4" -1 1/2" PVC elbow

Warranty: 1 Year
*Batteries Sold Separately

Link2O™ will constantly monitor conditions, and send you text messages or emails when your basement is in danger of flooding. At home, or across the globe, you can check and test system status anytime.

Performance Per Charge with BAT75*:
6 Days (11,500 GAL/11.5 Hour Continuous)
Performance Per Charge with BAT40*:
2.5 Days (4800 GAL/5.0 Hour Continuous)
Max Flow: 46 GPM
Flow @ 10': 21 GPM
Max Lift: 15'

Features: Link2O Remote Monitoring Capable. Pre-Plumbed. 1/2HP Primary Pump with Vertical Float Switch.

Includes: Internet gateway, backup pump, reed activation switch, AC power supply, integrated control panel and battery case.

Integrated Plumbing - includes 90° elbow, wye and 2 check valves.
Warranty: 2 Year

*Batteries Sold Separately

INSTALLATION KIT FOR BACKUP SYSTEMS

Rubber hose coupling with 2 inserts and 2 clamps. Slip reducer bushings (2 1-1/2 x 1-1/4 PVC). PVC tee (1-1/2 x 1-1/2 slip x 1-1/4 FNPT). PVC slip coupling (1-1/2 x 1-1/2). PVC pipe nipple (1-1/4 NPT x close). Check valve assembly (1-1/4 FNPT x 1-1/4 FNPT). Auxiliary check valve.

#PS198-270

SUMP PITS & SUMP PUMP ACCESSORIES



60162-1

FPW73-19-P2 with Lid



FP00012-6U-P2-01

Description	Part Number
CNBC Sump Pit - 23" x 30" H, 52 gal, undrilled lid	60162-1
CNBC Sump Pit - 23" x 30" H, 52 gal, lid with grommets	60162-2
Sump Basin Only - 18" x 22" H, 20 gal	FPW73-19-P2
Lid For FPW73 Sump Basin - 18" diameter	FPW73-20-P2
Check Valve - 1 1/4" MPT x 1 1/4" Barb or 1 1/2" Slip	BSC125B
Check Valve - 1 1/2" MPT x 1 1/4" Barb or 1 1/2" Slip	BSC150B
Mechanical Sleeve Coupling Inline Check Valve 1 1/2" x 1 1/2" Rubber Boot. ABS construction with straight flexible rubber sleeves on both the inlet & outlet side of the valve. Full port, flapper opens 100% and prevents debris from building up. Includes 4 all stainless steel clamps.	BSC150SB
Discharge Hose Kit - Includes 24' of universal fit sump pump tubing (1 1/4"), 2 high impact adapters (1 1/4" & 1 1/2"NPT, barbed) & hose clamp.	FP00012-6U-P2-01
Flexible Rubber Coupling - 1 1/2" x 1 1/2"	3625-003

ABOVE GROUND EFFLUENT PUMPS

HP	Max GPM	Max Head	Solids Handling x Discharge	Volts	Cord	Part Number
1/2	38	60'	.225" x 1 1/4"	115	10'	MDPC
1/2	45	50'	.225" x 1 1/4"	115/230	20'	621815 (BES50)



MDPC

Myers



621815

Little GIANT

SUBMERSIBLE EFFLUENT PUMPS

HP	Max GPM	Max Head	Solids Handling x Discharge	Operation	Volts	Cord	Part Number
CAST TOP, PLASTIC INTAKE							
1/3	50	22'	1/2" x 1 1/2"	Integral Snap Action Float	115	20'	506804
4/10	80	32'	3/4" x 1 1/2"	Automatic	115	20'	509209
4/10	80	32'	3/4" x 1 1/2"	Manual/ Automatic	115	20'	ME40120T
ALL CAST							
1/2	65	31'	3/4" x 1 1/2"	Automatic	115	20'	620187
1/2	87	44'	3/4" x 2"	Automatic	115	20'	ME45AC-11

Little GIANT

Myers

Note: All automatic pumps come with a piggyback mechanical float switch



506804



509209



ME40120T



ME45AC-11



620187

LIQUID LEVEL PUMP SWITCH - SJE PUMPMASTER® MECHANICALLY ACTIVATED WITH WIDE ANGLE FLOAT SWITCH

Switching Action	Cable Length	Piggyback Plug	HP at Volts	Ø / Hz	Part Number
Non Potable Water & Sewage Applications					
Pump Up	30'	No Plug	1/2 HP at 120 VAC, 1HP at 230 VAC	1 / 50-60	1010930
Pump Down	15'	No Plug	1/2 HP at 120 VAC, 1 HP at 230 VAC	1 / 50-60	1005685
Pump Down	15'	120VAC	1/2 HP at 120 VAC, 1 HP at 230 VAC	1 / 50-60	1002715
Pump Down	30'	No Plug	1/2HP at 120 VAC, 1HP at 230 VAC	1 / 50-60	1010931
Pump Down	30'	120VAC	1/2 HP at 120 VAC, 1 HP at 230 VAC	1 / 50-60	1002739
Pump Up or Down, 3 Wire	30'	No Plug	1/2 HP at 120 VAC, 1 HP at 230 VAC	1 / 50-60	1004841
Accessory - Pump Switch Cable Weight					
Wire / Cable Accommodated: SJOW, SJTW, SJTW 18/3, 16/2, 16/3, 14/2, 14/3					1002230

Pump down is normally open contacts for emptying. Pump up is normally closed contacts for filling. Switches used for direct wiring (without plug) may be used in either 120VAC or 230VAC applications within specified amp ratings.



LIQUID LEVEL ALARMS & ALARM CONTROL

Description	Activates On	Operation	Enclosure	Cord	Part Number
Tank Alert® AB Indoor Alarm	High Level	120 / 50-60 / 2.4	NEMA 1	6'	1011421
MySpy™ Wi-Fi Messenger - Indoor Alarm System	High Level or Under/Over Temperature	120 / 50-60 / 2.4 w/back up 9 VDC battery	NEMA 1	6'	1043586
Alert® XT Indoor & Outdoor Alarm	No float	120 / 50-60 / 7	Type 3R	-	1005836
SJE SignalMaster™ Alarm Control Switch	High/Low Level For up to 30' water depth	125-250 / 50-60 / 5	N/A	15'	1006095



1011421



1043586



1005836



1006095



Indoor Wireless Alarm with Auto Reset and Battery Backup Also Available!

HONEYWELL LYRIC™ WI-FI WATER LEAK & FREEZE DETECTOR

Description	Part Number
Temp, Humidity & Water Leak Detector. Works with the Honeywell Lyric App	CHW3610W1001
4' Cable Sensor	CHWES41013

- Part of Honeywell's trusted Lyric connected platform. It can be used as a stand alone product or part of a complete system.
- Connected by Lyric App, it alerts you on your smartphone when a leak is detected or the temperature drops below a temperature of your choice.
- Entire length of cable sensor detects water. Additional cables can be added to extend the sensor length to 500'.
- Easy setup, no wiring
- Features: Status LED lights & 100 dB buzzer
- Includes: 4' cable sensor & batteries

HONEYWELL WATER LEAK ALERT

Description	Part Number
Works with water heaters, sumps pumps and other HVAC applications. Includes: Water leak alert, 5' cable sensor, 2AA batteries & mounting hardware.	WHLDT1000

FLOODBUZZ™ WATER ALARM

Description	Part Number
Alerts of a leak - just place it anywhere you want leak detection. 110dB alarm, internal battery. Replace every two years or after unit is triggered.	FLOODBUZZ





RESIDENTIAL AIR INJECTION OXIDIZER

Chemical Free Backwashing Iron Filter
Featuring The Pentair 5810XTR2 Valve

Media Cu- bic Feet	Flow Rates US GPM			Mineral Tank Size	Part Number
	Service	Peak	Backwash		
1.5	5	10	5	10" x 54"	CFM1.55810XTR2AIO-B
2.0	8	15	8	12" x 52"	CFM2.05810XTR2AIO-B
Installation Accessories					
Bypass Assembly, 1.25"					43644
Connector Assembly, 1" NPT					61991-01



- ✓ High flow control valve with inlet check, advanced XTR2 touch-screen controller for unsurpassed filtration control & diagnostics
- ✓ Customizable and user friendly programming
- ✓ Captive area of oxygen or air
- ✓ Upper deflector to spread incoming flow of water through media
- ✓ Birm media included



ELECTRONIC WATER SOFTENERS

LOGIX 760 Controller Featuring The
GE Autotrol 255 Valve

Capacity Grains per cu. ft. dosage			Service Flow Rate GPM	Resin Tank Size	Resin Volume (cu. ft.)	Part Number
@15 lbs	@9 lbs	@3 lbs				
Cabinet Model						
32,000	25,000	15,000	5.0	10" x 35"	1.0	M255/760-CM30K
Twin Tank Models						
30,000	25,000	15,000	5.0	9" x 40"	1.0	M255/760-30K
38,000	34,000	17,000	6.25	10" x 40"	1.25	M255/760-40K
48,000	38,000	22,000	7.5	10" x 54"	1.5	M255/760-48K
64,000	50,000	28,000	10.0	12" x 52"	2.0	M255/760-64K
75,000	60,000	32,000	12.5	12" x 52"	2.5	M255/760-75K



- ✓ Sizes up to 120K Available
- ✓ Comes complete with bypass, adaptor kit and drain valve
- ✓ Davies Stocks A Full Line Of Softener Replacement Parts!

RESIDENTIAL REVERSE OSMOSIS DRINKING WATER SYSTEMS

Rated Output (GPD)	Vessels (Sumps)	Sediment Filter	Carbon Pre-Filter	Membrane	Carbon Post-Filter	Part Number
75	3	P5	C1 or GAC10	555693-00	K2533-KK	PV56T75-DSG
75	3	P5	C1 or GAC10	555693-00	C1 or GAC10	PRO46T75P
75	3	P5	C1 or GAC10	4002575	C1 or GAC10	GROHE75-D
75	3	Q5605	Q5633	TQ56-75FC	Q5633	PT4000T75-NA



PV56T75-DSG RO Includes:

- 3 gallon metal storage tank with bladder
- Chrome designer faucet
- John Guest fittings
- 75 GPD Membrane
- Sediment pre-filter, two pre-carbon filters, post-carbon filter
- All necessary hardware for installation



PRO46T75P Booster Pump RO Includes:

- Aquatech booster pump
- 3 gallon metal storage tank with bladder
- Chrome designer faucet
- John Guest fittings
- 75 GPD Membrane
- Sediment pre-filter, pre-carbon filter, post-carbon filter
- All necessary hardware for installation



GROHE75-D Water Saver RO Includes:

- 3 gallon metal storage tank with bladder
- Chrome designer faucet
- John Guest fittings
- 75 GPD Membrane
- Sediment pre-filter, pre-carbon filter, post-carbon filter
- All necessary hardware for installation

Water Saver RO saves 4X the water of conventional systems with a 1:1 ratio high recovery membrane!



PT4000T75-NA PuROTwist RO Includes:

- 3 gallon metal storage tank with bladder
- Standard lead free faucet
- John Guest fittings
- 75 GPD Membrane
- Omnipure® filters
- Sediment pre-filter, pre-carbon filter, post-carbon filter
- All necessary hardware for installation

Cartridges twist on & off for simple replacement!



RO ACCESSORIES

Description	Part Number
Low flow booster pump up to 50 GPD	6840-2J03-B221S
Tubing - 1/4" OD x 100'	PE-104
Tubing - 3/8" OD x 100'	360-6-100

ULTRAVIOLET STERILIZER

Voltage	Min Disinfection Flow Rate 40 mJ/cm ² @ 95% UVT Water	Chamber Dimensions	Connection Size Inlet / Outlet	Power Consumption	Flow Control to Add	Part Number
120 VAC	9 GPM	20 1/2" x 4"	3/4" MNPT	50W	FCGC-10NL	660089-R (D4 Premium)



- FEATURES:**
- LCD Controller
 - Visual Power On
 - Visual Lamp Life Remaining
 - Audible Lamp Failure
 - Audible Lamp Replacement Reminder
 - Temperature Management Valve
 - Solenoid Valve Optional

It is recommended to change lamp every year and sleeve every two years



Description	Part Number
Replacement Lamp & Sleeve Combo	602810-102
Replacement Lamp	602805
Replacement Sleeve	602732

RETENTION TANKS

Total Volume		Overall Height	Floor to CL Height	Dia.	System Connection		Part Number
Gal	Litres				Top	Bottom	
40	151	53.4"	1.75"	16.5"	1 1/4"	1 1/4"	FLU40EZ
80	303	64.1"	2.25"	21.4"	1 1/4"	1 1/4"	FLU80EZ



AIR PUMP & INSTALLATION KIT

Description	Part Number
115 Volt Air Pump. 75psi max, 100°F max.	617CA22
Installation Kit for 617CA22	617CAKIT



WATER FILTER CARTRIDGE HOUSINGS

Inlet / Outlet	Cartridge Size	Overall Dimensions	Max Temp / PSI	Flow Rate	Part Number
Standard Housing Package For Single Tap Applications					
Includes: Black filter head with pressure relief button, clear bowl, filter wrench, mounting bracket with hardware & O-ring					
3/4" FPT	2" x 10"	5" x 12"	120°F / 125	1-7 GPM	14HK-S10C-07
Big Blue Housing Package					
Includes: Black filter head with pressure relief button, blue bowl, filter wrench, mounting bracket with hardware & O-ring					
1" FPT	4" x 10"	7.28" x 14.05"	120°F / 100	1-20 GPM	14HK-G10B-10
High Temperature Housing Package					
Includes: Red filter head with pressure relief button, red bowl, filter wrench, mounting bracket with hardware & O-ring					
3/4" FPT	2" x 10"	5.35" x 12.48"	200°F / 125	1-10 GPM	14HK-HT10R-07
High Temperature Housing Package (Axiom)					
Includes: 304SS filter housing with brass head, brass drain valve with barb fitting and cap, two O-rings, opening tool & wall mounting bracket					
3/4" FNPT	2" x 10"	4.13" x 14"	250°F / 300	1-10 GPM	FH-10



14HK-S10C-07



14HK-G10B-10



14HK-HT10R-07



FH-10

HOT WATER FILTER CARTRIDGES

Type	Microns	Part Number
2" x 10"		
String wound, tin core suitable for general purpose high temp applications with water, oils, solvents, paint and other non-potable fluids	5	5
	10	10
	25	25





REPLACEMENT MEMBRANES

Fits RO#	Description	Part Number
E75TFC-3SF, EBP75TFCS-3SF PV56T75-DSG, PRO46T75P	75 GPD	555693-00
GROHE75-D	75 GPD	4002575
PT4000T75-NA	75 GPD Twist Off	TQ56-75FC



C1 GAC10 Q5633 P5

REPLACEMENT CARTRIDGES

Fits RO#	Description	Part Number
Pre & Post Carbon Cartridges		
E75TFC-3SF, EBP75TFCS-3SF PV56T75-DSG, PRO46T75P	2" x 10" Carbon Impregnated Cellulose	C1
GROHE75-D	2" x 10" Granular Activated Carbon	GAC10
PT4000T75-NA	2.5" x 12" Twist Off	Q5633
Sediment Cartridges		
E75TFC-3SF, EBP75TFCS-3SF PV56T75-DSG, PRO46T75P	2" x 10" Spun Bonded Polypropylene	P5
GROHE75-D	2" x 10" Spun Polypropylene	26222
PT4000T75-NA	2.5" x 12" Twist Off	Q5605



26222 S1 NCP-BB GAC-BB

SEDIMENT FILTER CARTRIDGES

Description	Microns	Part Number
2" x 10" Pleated Cellulose	20	S1
2" x 20" Spun Bonded Polypropylene	5	P5-20
4" x 10" Gradient Spun Polypropylene	5	DGD-5005
4" x 20" Gradient Spun Polypropylene	1	DGD2501-20
	5	DGD5005-20
	25	DGD7525-20



CARBON FILTER CARTRIDGES

Type	Microns	Part Number
4" x 10" Pleated Carbon Impregnated Polyester	10	NCP-BB
4" x 10" Granular Activated Carbon	-	GAC-BB
4" x 20" Radial Flow Granular Activated Carbon	-	RFC20-BB

COMMERCIAL, INDUSTRIAL & WHOLE-HOUSE REVERSE OSMOSIS SYSTEMS IN STOCK!



Product	Description	Part Number
Commercial Membranes	300 GPD, 2 1/2" dia. x 21" Long	1206799
	600 GPD, 2 1/2" dia. x 40" Long, Low Pressure	1206802
	2400 GPD, 4" dia. x 40" Long, Low Pressure	3056678
Vitec™ 3000 Membrane Antiscalant / Dispersant	45 lb, liquid antiscalant/dispersant designed to inhibit scale and disperse colloidal particles in cellulose acetate and thinfilm membrane separation systems.	V3000-45



Davies cleans commercial 4" x 40" RO Membranes in-house. Call for information & pricing!



Davies Will Set Up The Perfect Water Treatment System For Your Specific Application! Call For Proper Sizing & Design.



Visit our website:
www.daviessg.com

